


HEDA[®]
TOUGH WALL SYSTEM


STRONGARM[®]

SLIMWALL[®]
ENERGY EFFICIENT WALL SYSTEM



Nogging Brackets

Pre-punched and Pre-cut noggin brackets to suit a range of timber noggin sizes.



Heda tough wall system


High performance jamb and lintel system. Three profiles now available.




Boxed Studs

All gauges of Studco studs can be boxed to provide extra strength at door openings or where greater loads are required.

STEEL STUD SYSTEMS 0.50 - 0.55 BMT FRW*




Part No.	TOP & BOTTOM TRACK - 0.50mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
T5155H-30	Track 51 x 32mm with Safety Hem°	3000	10	100	1.44
T5155H-36	Track 51 x 32mm with Safety Hem°	3600	10	100	1.73
T6455H-30	Track 64 x 32mm with Safety Hem°	3000	10	100	1.60
T6455H-36	Track 64 x 32mm with Safety Hem°	3600	10	100	1.92
T7655H-30	Track 76 x 32mm with Safety Hem°	3000	10	100	1.92
T7655H-36	Track 76 x 32mm with Safety Hem°	3600	10	100	2.31
T9255H-30	Track 92 x 32mm with Safety Hem°	3000	10	100	2.13
T9255H-36	Track 92 x 32mm with Safety Hem°	3600	10	100	2.56




Part No.	DEFLECTION HEAD - 0.50mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
Only to be used in walls up to 2.7m high, otherwise use 0.75mm BMT.					
Also use 0.75mm BMT Deflection Head on staggered stud systems.					
DT645H-30	Deflection Head 64 x 50mm with Safety Hem°	3000	10	100	2.31
DT765H-30	Deflection Head 76 x 50mm with Safety Hem°	3000	10	100	2.48
DT925H-30	Deflection Head 92 x 50mm with Safety Hem°	3000	10	100	2.72

Unhemmed Track
Also Available
Made to order



Part No.	WALL STUD - 0.50mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
S5150-24	Stud 51mm x 0.50 BMT	2400	10	100	1.30
S5150-27	Stud 51mm x 0.50 BMT	2700	10	100	1.46
S5150-275	Stud 51mm x 0.50 BMT #	2750	10	100	1.48
S5150-30	Stud 51mm x 0.50 BMT	3000	10	100	1.63
S5150-33	Stud 51mm x 0.50 BMT #	3300	10	100	1.79
S5150-36	Stud 51mm x 0.50 BMT	3600	10	100	1.95
S6450-24	Stud 64mm x 0.50 BMT	2400	10	100	1.43
S6450-27	Stud 64mm x 0.50 BMT	2700	10	100	1.61
S6450-275	Stud 64mm x 0.50 BMT #	2750	10	100	1.64
S6450-280	Stud 64mm x 0.50 BMT	2800	10	100	1.67
S6450-30	Stud 64mm x 0.50 BMT	3000	10	100	1.79
S6450-33	Stud 64mm x 0.50 BMT #	3300	10	100	1.97
S6450-36	Stud 64mm x 0.50 BMT	3600	10	100	2.15
S6450-42	Stud 64mm x 0.50 BMT	4200	10	100	2.50




Part No.	WALL STUD - 0.55mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
S7655-24	Stud 76mm x 0.55 BMT	2400	10	100	1.71
S7655-27	Stud 76mm x 0.55 BMT	2700	10	100	1.95
S7655-275	Stud 76mm x 0.55 BMT #	2750	10	100	1.96
S7655-30	Stud 76mm x 0.55 BMT	3000	10	100	2.17
S7655-33	Stud 76mm x 0.55 BMT #	3300	10	100	2.35
S7655-36	Stud 76mm x 0.55 BMT	3600	10	100	2.61
S7655-42	Stud 76mm x 0.55 BMT	4200	10	100	3.04
S7655-48	Stud 76mm x 0.55 BMT	4800	10	100	3.41
S7655-60	Stud 76mm x 0.55 BMT	6000	10	100	4.27
S9255-24	Stud 92mm x 0.55 BMT	2400	10	100	1.91
S9255-27	Stud 92mm x 0.55 BMT	2700	10	100	2.15
S9255-275	Stud 92mm x 0.55 BMT #	2750	10	100	2.19
S9255-30	Stud 92mm x 0.55 BMT	3000	10	100	2.39
S9255-33	Stud 92mm x 0.55 BMT #	3300	10	100	2.63
S9255-36	Stud 92mm x 0.55 BMT	3600	10	100	2.87
S9255-42	Stud 92mm x 0.55 BMT	4200	10	100	3.35
S9255-48	Stud 92mm x 0.55 BMT	4800	10	100	3.83
S9255-60	Stud 92mm x 0.55 BMT	6000	10	100	4.78


* FOR USE IN FIRE RATED WALL SYSTEMS

° Unhemmed track available upon request.


STEEL STUD SYSTEMS 0.70 - 0.75 BMT FRW*



Part No.	TOP & BOTTOM TRACK - 0.70 BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
T5175H-30	Track 51 x 32mm with Safety Hem ^o	3000	10	100	2.04
T6475H-30	Track 64 x 32mm with Safety Hem ^o	3000	10	100	2.14
T7675H-30	Track 76 x 32mm with Safety Hem ^o	3000	10	100	2.37
T9275H-30	Track 92 x 32mm with Safety Hem ^o	3000	10	100	2.66
T1507H-30	Track 150 x 32mm with Safety Hem ^o	3000	10	100	3.94



Part No.	DEFLECTION HEAD - 0.70 - 0.75 BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
DT5175H-30	Deflection Head 51 x 50mm # with Safety Hem ^o	3000	10	100	2.80
DT6475H-30	Deflection Head 64 x 50mm with Safety Hem ^o	3000	10	100	3.02
DT7675H-30	Deflection Head 76 x 50mm with Safety Hem ^o	3000	10	100	3.21
DT9275H-30	Deflection Head 92 x 50mm with Safety Hem ^o	3000	10	100	3.54
DT1507H-30	Deflection Head 150 x 50mm with Safety Hem ^o	3000	10	50	4.64




Part No.	WALL STUD - 0.75 BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
S5175-27	Stud 51mm x 0.75 BMT #	2700	10	100	2.11
S5175-30	Stud 51mm x 0.75 BMT #	3000	10	100	2.34
S6475-24	Stud 64mm x 0.75 BMT	2400	10	100	2.14
S6475-27	Stud 64mm x 0.75 BMT	2700	10	100	2.41
S6475-30	Stud 64mm x 0.75 BMT	3000	10	100	2.67
S6475-36	Stud 64mm x 0.75 BMT	3600	10	100	3.21
S6475-42	Stud 64mm x 0.75 BMT	4200	10	100	3.74
S6475-48	Stud 64mm x 0.75 BMT	4800	10	100	4.28
S6475-6000	Stud 64mm x 0.75 BMT #	6000	10	100	5.34
S7675-24	Stud 76mm x 0.75 BMT	2400	10	100	2.33
S7675-27	Stud 76mm x 0.75 BMT	2700	10	100	2.61
S7675-30	Stud 76mm x 0.75 BMT	3000	10	100	2.90
S7675-36	Stud 76mm x 0.75 BMT	3600	10	100	3.48
S7675-42	Stud 76mm x 0.75 BMT	4200	10	100	4.05
S7675-48	Stud 76mm x 0.75 BMT	4800	10	100	4.63
S7675-6000	Stud 76mm x 0.75 BMT #	6000	10	100	5.69
S9275-24	Stud 92mm x 0.75 BMT	2400	10	100	2.55
S9275-27	Stud 92mm x 0.75 BMT	2700	10	100	2.87
S9275-30	Stud 92mm x 0.75 BMT	3000	10	100	3.19
S9275-36	Stud 92mm x 0.75 BMT	3600	10	100	3.83
S9275-42	Stud 92mm x 0.75 BMT	4200	10	100	4.47
S9275-48	Stud 92mm x 0.75 BMT	4800	10	100	5.11
S9275-60	Stud 92mm x 0.75 BMT	6000	10	100	6.39
S1507-36	Stud 150mm x 0.75 BMT	3600	10	100	4.98
S1507-42	Stud 150mm x 0.75 BMT	4200	10	100	5.81
S1507-48	Stud 150mm x 0.75 BMT	4800	10	100	6.64
S1507-60	Stud 150mm x 0.75 BMT	6000	10	100	8.29
S1507-72	Stud 150mm x 0.75 BMT	7200	10	100	9.95

Lead time and minimum quantities may apply

o Unhemmed track available upon request.

STEEL STUD SYSTEMS 0.70 - 0.75 BMT FRW*




Note: 0.70 BMT Noggins and Nogging Track are approved for use in 1.15 BMT Stud Systems

Part No.	NOGGINS - 0.70mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
<i>Individual Noggins cut to length for Fixing between Studs to overcome twisting of Studs.</i>					
N6475-45	64mm Notched Noggins	450	10	10	0.35
N6475-60	64mm Notched Noggins	600	10	10	0.47
N7675-45	76mm Notched Noggins	450	10	10	0.39
N7675-60	76mm Notched Noggins	600	10	10	0.51
N9275-45	92mm Notched Noggins	450	10	10	0.43
N9275-60	92mm Notched Noggins	600	10	10	0.57
N1507-45	150mm Notched Noggins	450	10	10	0.60
N1507-60	150mm Notched Noggins	600	10	10	0.80



**Noggin track also available:
- Custom centres
- Double punch to suit back to back wall studs**

Part No.	NOGGING TRACK - 0.70 - 0.75 BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
<i>Full Length Nogging Track Punched at 300, 450 & 600 Centres. Slide Studs in and Fix to overcome twisting of Studs.</i>					
NT6475-30-36	64mm Nogging Track - 300mm CTR #	3600	10	100	2.86
NT6475-45-36	64mm Nogging Track - 450mm CTR	3600	10	100	2.86
NT6475-60-36	64mm Nogging Track - 600mm CTR	3600	10	100	2.86
NT7675-30-36	76mm Nogging Track - 300mm CTR #	3600	10	100	3.15
NT7675-45-36	76mm Nogging Track - 450mm CTR	3600	10	100	3.15
NT7675-60-36	76mm Nogging Track - 600mm CTR	3600	10	100	3.15
NT9275-30-36	92mm Nogging Track - 300mm CTR #	3600	10	100	3.34
NT9275-45-36	92mm Nogging Track - 450mm CTR	3600	10	100	3.34
NT9275-60-36	92mm Nogging Track - 600mm CTR	3600	10	100	3.34
NT1507-30-36	150mm Nogging Track - 300mm CTR #	3600	10	100	4.86
NT1507-45-36	150mm Nogging Track - 450mm CTR	3600	10	100	4.86
NT1507-60-36	150mm Nogging Track - 600mm CTR	3600	10	100	4.86




Part No.	NOGGING BRACKETS	Sub pack	Stock pack	Approx kg/pce
M68	Nogging Bracket 36mm Intermediate	50	50	0.10
M69	Nogging Bracket 36mm End	50	50	0.04
M78	Nogging Bracket 18mm Intermediate	50	50	0.13
M79	Nogging Bracket 18mm End	50	50	0.07


Lead time and minimum quantities may apply

* FOR USE IN FIRE RATED WALL SYSTEMS


STEEL STUD SYSTEMS 1.15 BMT FRW*



Part No.	TOP & BOTTOM TRACK 1.15mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
T64115-30	Track 64 x 32mm	3000	1	100	3.47
T76115-30	Track 76 x 32mm	3000	1	100	3.82
T92115-30	Track 92 x 32mm	3000	1	100	4.27
T92115-65	Track 92 x 32mm #	6500	1	100	9.27
T15012-30	Track 150 x 32mm	3000	1	100	5.99



Part No.	DEFLECTION HEAD 1.15mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
DT64115-30	Deflection Head 64 x 50mm	3000	1	50	4.57
DT76115-30	Deflection Head 76 x 50mm	3000	1	50	4.98
DT92115-30	Deflection Head 92 x 50mm	3000	1	50	5.37
DT92115-6500	Deflection Head 92 x 50mm #	6500	1	50	11.63
DT15012-30	Deflection Head 150 x 50mm	3000	1	50	6.99



Part No.	WALL STUD - 1.15mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
S64115-27	Stud 64mm x 1.15 BMT	2700	1	100	3.39
S64115-30	Stud 64mm x 1.15 BMT	3000	1	100	3.79
S64115-36	Stud 64mm x 1.15 BMT	3600	1	100	4.52
S64115-42	Stud 64mm x 1.15 BMT	4200	1	100	5.28
S64115-48	Stud 64mm x 1.15 BMT	4800	1	100	6.03
S64115-60	Stud 64mm x 1.15 BMT	6000	1	100	7.58
S76115-27	Stud 76mm x 1.15 BMT	2700	1	100	3.71
S76115-30	Stud 76mm x 1.15 BMT	3000	1	100	4.13
S76115-36	Stud 76mm x 1.15 BMT	3600	1	100	4.95
S76115-42	Stud 76mm x 1.15 BMT	4200	1	100	5.78
S76115-48	Stud 76mm x 1.15 BMT	4800	1	100	6.60
S76115-60	Stud 76mm x 1.15 BMT	6000	1	100	8.25
S92115-27	Stud 92mm x 1.15 BMT	2700	1	100	4.11
S92115-30	Stud 92mm x 1.15 BMT	3000	1	100	4.57
S92115-36	Stud 92mm x 1.15 BMT	3600	1	100	5.48
S92115-42	Stud 92mm x 1.15 BMT	4200	1	100	6.40
S92115-48	Stud 92mm x 1.15 BMT	4800	1	100	7.31
S92115-60	Stud 92mm x 1.15 BMT	6000	1	100	9.19
S92115-72	Stud 92mm x 1.15 BMT	7200	1	100	10.97
S15012-36	Stud 150mm x 1.15 BMT	3600	1	100	7.66
S15012-42	Stud 150mm x 1.15 BMT	4200	1	100	8.67
S15012-48	Stud 150mm x 1.15 BMT	4800	1	100	9.91
S15012-60	Stud 150mm x 1.15 BMT	6000	1	100	12.38
S15012-72	Stud 150mm x 1.15 BMT	7200	1	100	14.86


Lead time and minimum quantities may apply

* FOR USE IN FIRE RATED WALL SYSTEMS

STEEL STUD SYSTEMS



Part No.	STUD AND TRACK 1.5mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
S92150-30	Wall Stud 92mm x 1.5mm BMT #	3000	1	100	6.02



Part No.	80mm DEFLECTION TRACK 1.15	Length mm.	Sub pack	Stock pack	Approx kg/pce
DT8050-30	Deflection Track 80 X 50mm x 1.15mm	3000	1	50	5.10
DT8050-36	Deflection Track 80 X 50mm x 1.15mm	3600	1	50	6.12
DT8050-60	Deflection Track 80 X 50mm x 1.15mm	6000	1	50	10.20




Part No.	STUDCO EZY-TRACK	Length mm.	Sub pack	Stock pack	Approx kg/pce
<i>EzyTrack is ideal for use in partitioning and steel stud applications - with a sliding strap.</i>					
FX51-2400	Studco EzyTrack 51mm x 0.55 BMT	2400	1	50	1.90
FX64-3000	Studco EzyTrack 64mm x 0.55 BMT	3000	10	100	2.07
FX76-3000	Studco EzyTrack 76mm x 0.55 BMT	3000	10	100	2.08
FX92-3000	Studco EzyTrack 92mm x 0.75 BMT	3000	10	100	2.12
FX150-2400	Studco EzyTrack 150mm x 0.75 BMT #	2400	1	50	2.54

BRACKETS



Part No.	ANGLE BRACKETS	Length mm.	Sub pack	Stock pack	Approx kg/pce
M100	Angle Bracket 100 x 45 x 40 x 1.5mm-6mm Hole	100	100	100	0.09



Part No.	SLOTTED DEFLECTION BRACKETS	Length mm.	Sub pack	Stock pack	Approx kg/pce
M103	Slotted Deflection Cleat	80	50	50	0.19



Part No.	HEDA BRACKET	Length mm.	Sub pack	Stock pack	Approx kg/pce
<i>Heavy duty structural wall brace for free standing walls.</i>					
M104	Slotted HEDA Connector		50	50	0.15

STRONGARM®



Part No.	STRONGARM BRACKET	Length mm.	Sub pack	Stock pack	Approx kg/pce
<i>Heavy duty structural wall brace for free standing walls</i>					
M110	Strongarm Wall Brace 1200mm	1200mm	1	1	10.20



Part No.	STAGGERED STUD CLIPS	Sub pack	Stock pack	Approx kg/pce
<i>To be used in Staggered Stud Systems</i>				
M126	Staggered Stud Clip for Track	100	100	0.02



Part No.	UNIVERSAL L BRACKET	Length mm.	Sub pack	Stock pack	Approx kg/pce
M545	Universal L Bracket x 1.5mm	75	50	50	0.09

* FOR USE IN FIRE RATED WALL SYSTEMS

Lead time and minimum quantities may apply

1800 STUDCO

STUDCO
BUILDING SYSTEMS

STEEL STUD SYSTEMS

SLIMWALL[®]

ENERGY EFFICIENT WALL SYSTEM



Part No.	WALL CHANNEL 0.5mm BMT	Length mm.	Sub pack	Stock pack	Approx kg/pce
M355-3000	35mm Ceiling Channel 0.5mm	3000	10	100	1.63
M355-3600	35mm Ceiling Channel 0.5mm	3600	10	100	1.95
M355-4800	35mm Ceiling Channel 0.5mm	4800	10	100	2.59




Part No.	SLIMWALL BRACKETS	Length mm.	Sub pack	Stock pack	Approx kg/pce
M163-6	Slimwall Bracket 69-92mm Cavity	68-90*	50	100	0.05
M163-8	Slimwall Bracket 85-108mm Cavity	82-108*	50	100	0.06

* This is the distance from the concrete substrate and the back face of the plasterboard lining.

HEDA[®]


TOUGH WALL SYSTEM




Part No.	HEDA JAMB63	Length mm.	Sub pack	Stock pack	Approx kg/pce
Header Jamb Sections - heavy duty jamb and lintel system.					
HJ9263150-285	Heda Jamb63 92 x 63mm x 16 x 1.50 BMT	2850	1	100	8.35
HJ9263150-30	Heda Jamb63 92 x 63mm x 16 x 1.50 BMT	3000	1	100	8.79
HJ9263150-36	Heda Jamb63 92 x 63mm x 16 x 1.50 BMT	3600	1	100	10.55
HJ9263150-48	Heda Jamb63 92 x 63mm x 16 x 1.50 BMT	4800	1	100	14.07

For HEDA Connector Bracket see page 24

Custom lengths
Also Available
Rolled to order



Part No.	HEDA JAMB90	Length mm.	Sub pack	Stock pack	Approx kg/pce
Header Jamb Sections - heavy duty jamb and lintel system.					
HJ9289155-285	Heda Jamb90 92 x 89mm x 25 x 1.55 BMT	2850	1	100	9.42
HJ9289155-36	Heda Jamb90 92 x 89mm x 25 x 1.55 BMT	3600	10	100	11.91
HJ9289155-48	Heda Jamb90 92 x 89mm x 25 x 1.55 BMT	4800	10	100	15.89



Part No.	RAPID TRACK	Length mm.	Sub pack	Stock pack	Approx kg/pce
Slotted Deflection Head Track - 0.75mm BMT					
DS6475-30	Slotted Deflection Head Track 64mm x 0.75 BMT	3000	10	100	3.02
DS7675-30	Slotted Deflection Head Track 76mm x 0.75 BMT	3000	10	100	3.21
DS9275-30	Slotted Deflection Head Track 92mm x 0.75 BMT	3000	10	100	3.54
Slotted Deflection Head Track - 1.15mm BMT					
DS76115-30	Slotted Deflection Head Track 76mm x 1.15 BMT	3000	10	100	4.98
DS92115-30	Slotted Deflection Head Track 92mm x 1.15 BMT	3000	10	100	5.29
DS150115-30	Slotted Deflection Head Track 150mm x 1.15 BMT	3000	10	100	5.29

Lead time and minimum quantities may apply

STEEL STUD SYSTEMS